



750 American Blvd. - St. Joseph TN 38481

Voice: (877) 597-8300

Web: www.utimachinery.com Email: utimachinery@gmail.com

ID#: 30532

2014 Haas HRTA6 CNC Rotary Table

TABLES, N/C & CNC

Spindle: Maximum Speed	0.001 - 100°/sec
Maximum Torque	210 ft/lbs
Runout Maximum	0.0005"
Backlash	30 Arc-sec
Through Bore	2.03"
Center Height	6" +/- 0.001"
Gear Ratio	90:1
Timing	2:1
Tooling	A1-6 Spindle
Indexing: Maximum Rotation/Step	999,999°
Resolution	0.001°
Accuracy (+/-)	15 arc-sec
Repeatability	10 arc-sec
Worm Gear Diameter	6.3"
General: Power Requirement	115 VAC @ 15 A
Air Pressure Maximum	120 PSI
Operating Temp (max ambient)	100° F
Duty Cycle full/low speed	50/100%
Weight: Brushless Control	14.2 lbs
Table	165 lbs
Purchased opts: 5C Collet Adapter	
Air Collet Closer, Pneumatic Draw-Tube Assembly, 1.75" Through Hole	
8" A1-6 Top Reversible 3-Jaw Chuck	
Pneumatic Tailstock, 6" center height	
Rotary was purchased and installed in mid 2014. The contract	
requiring the rotary did not work out so the rotary was removed and is	
basically unused, Like new condition.	

[Click Here to Request Quote](#)

Haas CNC Rotary Table, HRTA6, Same Size as a Haas HRT210, HRT-210. Larger than HRT160, HRT-160. Smaller than the HRT310, HRT-310 and HRT450, HRT-450

UTI Machinery

750 American Blvd. - St. Joseph TN 38481

Voice: (877) 597-8300

Web: www.utimachinery.com Email: utimachinery@gmail.com

ID#: 30532

2014 Haas HRTA6 CNC Rotary Table

TABLES, N/C & CNC

30532



30532



UTI Machinery

750 American Blvd. - St. Joseph TN 38481

Voice: (877) 597-8300

Web: www.utimachinery.com Email: utimachinery@gmail.com

ID#: 30532

2014 Haas HRTA6 CNC Rotary Table

TABLES, N/C & CNC

30532



[Click Here to Request Quote](#)